## Comprehensive Finished Street Name Signs Checklist

#### Roadway Type Local Two Lane Roads 0-25 MPH Easy Order Checklist: MUTCD guidance - Initial upper-case letters at least 4" high and lower-case letters 3/4 height of upper-case. Custom Dr Blade Height: 6" | Corner Radius .75" 8 Dimensions Select Blade Maple St Letter Height/Prefix: 4" | Suffix Height: 2" ☐ Flat Blade .080" Aluminum Font: Highway Gothic B | Case: U/L Custom Dr ☐ Extruded Blade NO RADIUS Blade Height: 8" | Corner Radius .75" 6" and 9" Blade Heights Only Hickory La Letter Height/Prefix: 4" | Suffix Height: 2" ☐ Econo Vandal Resistant Font: Highway Gothic B | Case: U/L 3MM ACM MATERIAL - NO SCRAP VALUE Two Lane Roads Over 25 MPH and Multi Lane Roads 0-40 MPH 6", 8" and 9" Blade Heights Only MUTCD guidance - Initial upper-case letters at least 6" high and lower-case letters 3/4 height of upper-case. Blade Height: 9" | Corner Radius .75" 2 Reflective Type Second St Letter Height/Prefix: 6" | Suffix Height: 3" ☐ High Intensity Prismatic Font: Highway Gothic B | Case: U/L MUTCD guidance - For ground and overhead mounted signage: White reflective must be > Blade Height: 12" | Corner Radius 1.5" Seventh st 120 candlepower, Green must be > 7. Letter Height/Prefix: 6" | Suffix Height: 3" Font: Highway Gothic B | Case: U/L Custom Dr Color Scheme Multi Lane Roads Over 40 MPH ☐ White on Green Custom or MUTCD guidance - Initial upper-case letters at least 8" high and lower-case letters 3/4 height of upper-case. White on Blue Blade Height: 12" | Corner Radius 1.5" ☐ White on Brown Cherry Letter Height/Prefix: 8" | Suffix Height: 4" ☐ Black on White Font: Highway Gothic B | Case: U/L ☐ White on Black □ Other/Custom **Overhead Mast Arm** MUTCD guidance - Initial upper-case letters at least 12" high and lower-case letters 3/4 height of upper-case. MUTCD guidance - Acceptable alternative background colors to Green are Blue, Brown or White. The legend shall be White, except for Black on White signs. Custom colors require adequate contrast, call a customer service specialist for guidance. Blade Height: 18" | Corner Radius 1.5" Hillside Dr Letter Height/Prefix: 8" |Suffix Height: 8" 4 Sides Font: Highway Gothic C | Case: U/L ☐ **Double Face** Ground Mount ☐ Single Face Overhead Mount E Tombigbee St Blade Height: 18" | Corner Radius 1.5" MUTCD guidance - Borders are **5** Border optional, but if used, must be the Letter Height: 8" | Prefix/Suffix Height: 4" same color as the letters □ None Font: Highway Gothic C | Case: U/L ☐ **Edge** - Should use on dark backgrounds ☐ **Inset** - Should use on white backgrounds Holly Ct **6** a. **Logo or Route Symbol**MUTCD guidance - Route symbols or Logos Blade Height: 24" | Corner Radius 1.5" Letter Height/Prefix/Suffix Height: 12" ☐ None may be placed on the left side of a sign. Font: Highway Gothic C | Case: U/L ☐ Yes The maximum height is the same as the letter height. **6** b. **Prefix/Suffix** MUTCD Guidance - Prefix/Suffix Height ☐ Full Size may be smaller than the height of the primary copy and may be abbreviated. No punctuation is to be used. Blade Height: 24" | Corner Radius 1.5" **5** Terry Letter Height/Prefix: 12" | Suffix Height: 6" Logo/Route Symbol Height: 12" Font: Highway Gothic C | Case: U/L **7** Vandal Resistant Hole Punch □ None Street Name Signs MUST be Type II copy on Type I background or better. □ VPA 12 Bolt thru We recommend using **3M** High Intensity Prismatic for Ground Mounted SNS □ Other and **3M** Diamond Grade Cubed for Overhead Mounted SNS

### **IMPORTANT NOTE:**

Please e-mail or fax your list of signs (MUST BE A TYPED LIST), along with the specifications you've selected above for a personalized quote. Prefixes/Suffixes MUST use MUTCD Abbreviation, No Punctuation, Special Characters or Block Numbers allowed. Street Name Signs are Priced based on Length.

Distributed by:		







# The SNS STANDARD Finished Street Name Sign Designs are a Top Seller and are MUTCD Compliant.

The SNS Standard Street Name Sign Design is a top selling choice for easy ordering plus offers faster shipping than choosing your own options from the comprehensive list of available MUTCD compliant

## **Standard Finished Street Name Sign Checklist**

### QTY: 6"Tall Sign Blades SPEED **♦** Roadway Type: Local Two-Lane LIMIT for use on low volume roads with **Speed Limits of 25 MPH or less** SNS STANDARD PRODUCT ID: M1CPC(06XX)FHA(CCCC) ◆ Flat Blade: (06XX) 6" x variable lengths (36" MAX) .080 Aluminum | No Hole Punch | .75" Corner Radius Letter Height: 4" Prefix | 4" Primary | 2" Suffix Letter Font: Upper/Lower Case Highway Gothic B Sign Border: NONE Reflective Sides: Double-Sided Reflective Sheeting Type: N Custom Signs Dr High Intensity Prismatic N Custom Signs Dr Color Scheme: ☐ White on Green N Custom Signs or ☐ White on Blue ☐ White on Brown N Custom Signs Dr ☐ Black on White N Custom Signs 📭 ☐ White on Black Retroreflectivity Management: Would you like to implement an minimum retro-reflectivity assessment method, at no extra

### **IMPORTANT NOTE:**

□ No

Please e-mail or fax your list of signs (MUST BE A TYPED LIST), along with the specifications you've selected above for a personalized quote. Prefixes/Suffixes MUST use MUTCD Abbreviation, No Punctuation, Special Characters or Block Numbers allowed. No Design Proofs are provided with Standard Finished Street Name Design Orders. Street Name Signs are Priced based on Length.

MFG MMYY

Expiration Date

EXP MM/YY

charge? (Placement: Bottom Right Hand Corner)

☐ Yes Manufacturer Date

SPEED LIMIT
D: 40
ole lengths (42" MAX) ch   .75" Corner Radius rimary   3" Suffix
se Highway Gothic B
N Custom Signs D
N Custom Signs
nt: an minimum method, at no extra Hand Corner)